# CE-400

Automatic Wastewater Treatment

### **Standard Features**

- Fully Automatic Operation with Manual Overrides
- Maximum Throughput: 1200 gph
- 400-Gallon Treatment Tank
- Allen Bradley Micrologix PLC Controls
- U.L. Approved Control Panel
- 3 Horsepower Heavy Duty Agitator with Jet Basket
- Treatment Tank Auto Washdown
- Pre-Plumbed for Effluent Pump
- Automatic Chemical Feed System with 300 lb. Hopper,
   Complete with 2000 lb. Superbag Support Frame
- Double Rollers for Greater Dewatering
- Equipment Measurements: Length: 10'4", Width: 7'4", Height: 11'11", Weight: 5,000 lbs.

## **Optional Features**

- 3.0 Cubic Yard Dumpster with False Bottom for Dewatering
- $\bullet\,$  pH Control System for Treatment Tank
- Stainless Steel Construction
- 2" Cast Iron Influent Diaphragm Pump
- 2" Aluminum Effluent Diaphragm Pump
- Auto Washdown for Filtrate Tank
- Equalization and Reuse Tanks



Ringwood's wastewater treatment units optimize the use of clay based flocculants to clarify industrial wastewaters.

Ringwood


Ringwood Environmental, Inc. Wastewater Products
6715 West 73rd Street • Bedford Park, IL 60638 • 708.458.6000 • FAX 708.458.1051


# CE-400

## Ringwood

#### Automatic Wastewater Treatment

NOTE: Items in RED are standard equipment that can be located on either side of the CE-400. Items in BLUE are optional equipment.





### **Service Requirements**

- **E** 480 VAC, 30 AMP, Grounded, 3 Phase Power Terminated at the Disconnect in the CE-400 Control Panel.
- **A** 1" FNPT Air Supply Connection. 80-100 PSI, Clean, Dry, Air Required, With Locking Handle Valve on Service Line.
- **W** 1" FNPT City Water Supply Connection. 30 PSI Required, With Locking Handle Valve on Service Line.
- I 2" FNPT Influent Water Inlet Connection.
- **F** 2" MNPT Effluent Water Discharge Connection.

## Ringwood Environmental, Inc. Wastewater Products